SMALL BATCH CONTAINMENT POWDER WEIGH & SAMPLE BOOTH



NOTE:

- All filters are PSL challenged at factory. Unit performance meets Fed. Std. 209E/ISO 5, ASHRAE Std and IES-RP-CC-002
- Meets all applicable OEL band exposure levels
- USP 979 COMPLIANT
- All electrical wiring is in conformance with NEMA and NEC standards.
- Isolation Systems, Inc. inspection reports available upon request.

STANDARD FEATURES

- Formed 16 ga 304 stainless steel construction with #4 finish.
- Work surface 14 ga 304 stainless steel
- Frame 2" sq. 14 ga 304 stainless steel structural frame with #4 finish with 6" sq. foot plates.
- Horizontal flow intake HEPA filtration 99.99% efficient @ .3 microns . With gel seal to plenum.
- Bag out HEPA
- Merv 8 pre filtration
- Vertical bar 304 stainless steel removable protective grilles for all exposed filter media.
- 304 stainless steel side walls with service access.
- Incrementally adjustable vertical sliding sash 1/4 "glazing in SS frame. Position locking standard
- Sanitary adjustable 304 SS leg levelers
- Flush mounted fluorescent lighting
- Magnehelic gages to monitor system and filter pressure differential.
- Removable side access panels for service installation
- Lighted power and lighting on/off switches.
- Variable solid state blower speed control.
- Electrical: 120V / 60HZ / 1ph.

OPTIONAL FEATURES

- 316L stainless steel construction.
- ULPA filtration 99.9995% efficient @ .12 microns.
- Optional voltages in 208/230v-60hz-1ph, and 460v-60hz-3ph. (50 hz motor rating also available).
- Custom sizes and configurations.
- Variable frequency drive motor speed controls.
- Anti Static sash panel
- Audible visual low pressure/flow alarm.
- Class 1 Div 1 explosion proof.
- Electrical outlets.
- Pre Installed service connections
- 10" dia duct collar for exhaust extraction
- 304 SS swivel type locking casters with non-Marring polyurethane wheels

MODEL #	WORK AREA DIM	OA H	OA D	OA W	W/S AFF	SHIP WT
SBHC-304	24"d x 48"w x 30"h	66/72	36	56	30/36	550 lb
SBHC-364	24"d x 48"w x 36"h	72/78	36	56	30/36	695 lb
SBHC-305	24"d x 60"w x 30"h	66/72	36	68	30/36	830 lb
SBHC-365	24"d x 60"w x 36"h	72/78	36	68	30/36	885 lb
SBHC-306	24"d x 72"w x 30"h	66/72	36	78	30/36	930 lb
SBHC-366	24"d x 72"w x 36"h	72/78	36	78	30/36	975 lb

all catalog dimensions are nominal

All information herein is subject to change without notice.

All shipping weights are estimated



Revised 11/2015